

Conbraco 16XT Hydronic Expansion Tanks



Overview

Conbraco non-potable expansion tanks help maintain balanced pressure throughout a hot water heating system by absorbing thermal expansion. Pre-pressurized, they're designed to prevent system damage and unnecessary discharges by relief valves and ensure long, trouble-free system life.

Features

- Welded steel construction
- Rugged flexible diaphragm
- Pre-charged at 12 psig
- Compact design saves energy and space
- Glycol compatible
- Maximum working pressure: 150 psig
- Ideal for peak use systems such as car washes, processing plants, hotels/motels, commercial laundries
- Pressure relief valves relieve excess pressure in cold water storage tanks and water supply lines.

Specifications

Part No.	A in./mm	B in./mm	WT/100 lbs/kg	Connection	Capacity gal/liter	Exp Vol gal
16-XT1-01	10.880 276.352	8.000 203.200	5.500 2.495	1/2" N PT	2.110 9.402	1.770
16-XT3-01	13.750 349.250	10.750 273.050	8.100 3.674	1/2" N PT	4.760 21.211	3.990
16-XT5-01	15.880 403.352	12.000 304.800	9.700 4.400	1/2" N PT	6.340 28.251	5.310
16-XT7-01	20.000 508.000	15.000 381.000	23.400 10.614	1/2" N PT	13.210 58.864	11.060

